A Prototype of Autonomous Vehicle Using Stereoscopic Vision

Sumit Aher, Pulkit Bakaya, Raees Mulla

K.K.Wagh Institute of Engineering Education & Research, SavitribaiPhule Pune University, Nashik
sumitsaher@gmail.com, pulkitbakaya@gmail.com, raeesmmulla@gmail.com

Abstract— In today's developing world, technology is growing day by day and expanding its roots towards development of autonomous vehicles. The existing autonomous vehicles have their limitations that restricts their application only to particular areas which have well-built roads with lane markings and road signs. This incurs a huge development cost. The proposed system focuses on implementing a prototype of autonomous vehicle using stereoscopic vision. This model can be used as a reference to overcome the issues of existing systems, by improving the accuracy and efficiency of autonomous vehicle for better safety. Stereoscopic vision is used to get input from environment on which image processing algorithms are applied to obtain the improved response time for autonomous vehicle.

Keywords— autonomous, stereoscopic vision, homographic vision, obstacle analyzer

INTRODUCTION

The smart automobile/ the autonomous car is one step towards smart city and is applicable for all the handicap people especially blind people and is suitable for all day to day transport activities. The motive behind the whole concept of the driverless car was to avoid accidents that take place now days in large numbers. According to the statistics of 2014, [1] the death rate of people due to accidents in the US was around 32,000 each year. In India itself, the count was around 13,976. Use of these Smart Automobiles on the roads could reduce at least half of these accidents, it could save up to 16,000 lives each year. Also, the handicapped and older public can avail to long distance transport without relying on a third person say, a driver. All they would have to do is set the destination on the GPS and the car will take them to that destination.

With the continuous progress and evolution in information technology and rising demands of safe travel, it is necessary to find better and innovative systems to aid the human life and make it easier. There has been a tremendous growth in the technologies involving self-driving

cars including LIDAR (Light Detection and Ranging) to Image Processing techniques which has led self-driving car to become a reality in 2016.

Self-Driving cars are applicable in a lot of areas including Industrial transport, Public transport, Military ammunition supply and Ambulances. The industrial applications include all the conveyer activities being done in industries for goods transportation in intra infrastructure of the industries. Public

transport for intra cities such as cabs can be replaced with Smart Cabs which will help increase strict obedience of traffic rules and decrease the number of accidents taking place in India especially due to cabs and also ensure safety and security of passengers travelling in night especially females. Self-driving ambulances may help focus paramedics on treating patients in an emergency.

It would help enforce many of the constraints for efficient and reliable road transport such as:

Fuel conservation can be done at maximum by efficient driving techniques and speed limits

Strict obedience of traffic rules especially in India as many of the human drivers ignore and neglect the traffic rules such as not following of traffic signal lights, improper lane keeping, not following of speed limits especially in city areas, blowing horns in horn restricted areas such as near educational institutes and organizations etc.

Efficient use of parking space can be achieved using autonomous cars as they include automated parking algorithms and sensors to avoid collision with other parked vehicles which will in turn increase space for parking.

There is an increased demand for these cars in India itself. This is due to the careless attitude of drivers (in the city, as well as on highways and mountain passing). As of 2014, [1] deaths due to speeding reached a count of 57,844 while that due to overloaded trucks on highways totalled up to 36,543 deaths. Hence, introduction of these self-governing and self-driving smart automobiles in India will help reduce this death toll as well as aid in day to day activities like long distance goods transport, disciplined driving and so on. Autonomous cars will soon be a reality; the only question is how quickly, as the number of technologies involved for its implementation are growing day by day.

Related Work

Autonomous cars have been said to be the next big innovation in coming years in India, it is supposed to have a massive social impact in all kind of fields.

According to Marlon G. Boarnet's research findings, who is a specialist in transportation and urban growth at the University of South California [1] say that for approximately every two generations, they would reconstruct the transportation infrastructure in their cities in a way that will shape the vitality of the neighborhoods; the settlement patterns of our cities and countryside; and our economy, society and culture" and as everyone believes self-driving cars are the new big change everyone is talking about. It will not only impact environment such as by improvement in fuel economy. It would help decrease the fuel consumption by 20% to 30% approx.

Ericco Guizzo, in his presented journal paper titled [2] "How Google's self-driving car works" stated the key functions or objectives for the self-driving vehicles. This included the implementation of LIDAR systems for 360% image production and mapping, obstacle detection systems to avoid collisions with other cars. It also explained the parking assistance systems and most importantly the lane keeping management which is carried out by the self-

driving car itself without human interference. Guizzo's research findings also showed a couple of backdrops like the high cost of LIDAR systems which in turn increases the cost of vehicles implementing LIDAR sensors and the self-driving car's inefficiency in adapting to dynamically changing environments. Most of the time the environment and infrastructure like roads, speed breakers, traffic signal lights, addition of new lanes makes it difficult to adapt itself to changing environments as it requires prior knowledge of the roads and its infrastructure for autonomous driving.

In study done by Christoph Stiller and Keith Redmill who had presented, [3] ideas and possibilities of autonomous vehicles being able to detect and avoid obstacles and analyze and estimate the nearby objects or obstacles. The major problem with this finding was the unreliability of the complete system due to its sole dependence on only RADAR sensors. It makes it inefficient as sole reliance on a single system may cause collision with other vehicles if it fails to detect an object.

According to Jing Fu, and his colleagues in there presented paper in the IEEE spectrum in 2014 [4] he enlightened 2 new advancements in the driverless vehicle's capacity to sense and navigate the environment and also manipulate the car's speed using a 'Wheel Speed Sensor' and Radar sensors along with a navigation system built to strongly support the autonomous behavior or the driverless car. This research will help coping with the speeds of other non-autonomous vehicles to avoid collision with each other in heavy road traffic areas. The wheel speed sensor works on an image processing algorithm along with radar sensors.

On the other hand, city traffic can be a problem for the self-driving vehicles and safety is a major issue of the current era. This has always been a big concern for the developers of the driverless car, on how to make the car safer for city travel. Andrei Furda, and his colleagues Laurent Bouraoui, Michel Parent and Ljubo Vlacic presented ideas on using VANET systems for intra-vehicular and inter-vehicular communications in their research paper [5]Their research showed great potential as networking of autonomous vehicles will help self-learning which can be used by other vehicles in similar situations, intra-vehicular communication will help increase safety and security of the vehicle by automatic checking and communication between all the modules used for autonomous vehicles implementation, although it was only applicable in areas where sensors and VANET(Vehicular network) systems were deployed.

In the research by Vicente Milanes, Enrique Onieva, Joshue Perez, and Jorge Godoy, their research findings on [6]how the driverless car can perform computerized or automatic lane-keeping and make suitable decisions while running on high speeds on highways. This survey also showed the system's dependency on semi-automated cars only, which can evolve to support the fully-automated systems too.

It was stated in the research paper on Milos Mladenovic and Montasir Abbas that the [7] driverless vehicles need an efficient and fail proof framework to handle and govern the control unit and statistical analysis of surroundings and obstacles. The car needs to perform auto computation of any obstacles that might occur and perform actions accordingly while the control framework which handles all the self-governing capability of the driverless car.

In research done by G.R. Dunlop and M. Jufer back in 1998 to showcase their ideas and developments on [8] making the driverless cars truly driverless by proposing auto steering of the passenger vehicle using magnetic sensors while, it also showed research on how the car will be controlled while turning on corners with accuracy just like any human driver.

Thus, from all these research findings and ideas it can be derived that the motivation behind smart automobiles has been going on since a long time, and it is not just a myth but a promising vision. Autonomous vehicles will soon be a future of India and help to tackle many

concerns related to road traffic infrastructure such as avoidance of accidents, not following of traffic rules etc.

Autonomous Vehicles developed till date do not possess dynamicity and are not capable of successful deployments in Indian traffic road infrastructure. But given the available human resource and rapidly evolving technology we can hope to see Autonomous Vehicles running on Indian Roads either as Public Transport such as Cabs, buses, auto-rickshaws etc., as Industrial conveyer transport vehicles and inventory supplying trucks, or as an aid to the specially abled people and as Paramedic Vehicles etc.

Methodology

Algorithm
1) User starts the car engine.
2) Pre-initialization checks are performed on startup.
3) Validate all the modules and sensors and wait for input from user.
4) User sets source & destination data via GPS.
5) The GPS sends this data to location mapper module.
6) The control unit draws or maps a path to be followed by automobile.
7) Pass data from steps 2, 3 & 4 to steer control and management software.
8) Initialize traffic-awareness, obstacle detection module.
9) Automobile should start moving accordingly.
10) Camera constantly captures images of the road signs, lanes, street lights to image processor.
11) Sensors and radars notify control unit about oncoming obstacles.
12) Take suitable actions for lane-keeping, collision avoidance and safe driving.
13) Notify driver on reaching destination.
14) Initiate park assist module.
15) Stop engine.

Result

Mathematical Model
This mathematical model described using the set theory as a superset S which consists of 3 subsets namely:

Therefore, S= {I, O, F}

I = {set of inputs provided to or acquired by the system},
O = {set of outputs to state the corresponding response given by the various modules or the system as a whole}
F = {a set of functions or software modules used for acquisition, processing and generating suitable responses and/or corresponding actions of the proposed system}.

Consider a set T = {T1, T2…..Tn} that contains all the devices that provide data and signals to the processor.

Let set T1 = {images captured via camera}

Let set T2 = {object 1 detected via radars and sensors}
Similarly T2, T3…. Tn contain 'n' objects that are detected by the various collision detection modules.

Therefore T= T1 $\cup$ T2 $\cup$ T3 $\cup$….. $\cup$Tn.
T= {T1, T2, T3…….. Tn}

Thus set T $\subseteq$ I.
Let set Q be the set of signals generated from each element of set T.
Q = {captured sensor/radar inputs, pathway images, camera feed, source location, destination location}
Thus Q $\subseteq$ T.
Hence input set I= {T, Q}.

Let a particular set D contain all the analyzed values after processing the inputs and generating corresponding actions say D1, D2….. up to Dn.

D= {collision prevention, computer generated and guided path from source to destination, hands free transportation, traffic awareness of vehicle while in motion, safe travel }
Therefore D $\subseteq$ O.

A set E points to the control software that actually drives the car, makes it stop or perform other actions.
E= {move car (forward, reverse), turn (left/right), stop car, adjust velocity}

Hence the output set O= {D,E}.

Now, all the collected inputs that are to be processed and analyzed are to be performed via some user defined functions. The functions belong the set F= {F1,F2…. Fn} for n user defined functions.

Hence F= {image processing module, obstacle detection module, lane_keeping(), path_monitor(), collision avoidance module, self-drive module, location_mapper() }

Thus, the overall system follows the above mentioned subsets for its working and this is combines in one single superset that is set S={I,F,O}. Using these I/O and functionality models, the SMART Automobile is to be designed to achieve its objectives.

Conclusion

In conclusion, there are many strong socio-economic motivators for adopting the smart automobiles such as human safety, infrastructure efficiency, quality of life, physically challenged people as they can use self-driving car for their commuting. These are just a few of the key concerns that will help to make autonomous car a reality. With the rapid growth in technology the existing as well the emerging manufacturers of this automobile will ensure a reliable and quality performance. These features combined with strong economic motivators are sure to overcome such obstacles. The future will surely include autonomous vehicles in India too.

REFERENCES

[1] Marlon G. Boarnet's "A review and analysis of literature survey of Autonomous Driving cars", IEEE Spectrum www.micharlbartl.com/co-creation/wp-content/uploads/Lit-Review-AD_Mol.pdf

[2] Ericco Guizzo- "How Google's Self-Driving Car Works IEEE Spectrum"., IEEE spectrum Retrieved *February 26, 2013.*

[3] Christoph Stiller and Keith Redmill -"Systems for safety and Autonomous Behavior" IEEE *February 2007.*

[4] Jing Fu, Tao Mei, Hui Zhu Huawei Liang and Biao Yu -"Research on wide range localization for driverless vehicles in outdoor environment based on particle filter" IEEE Spectrum 2014.

[5] Andrei Furda, Laurent Bouraoui, Michel Parent and Ljubo Vlacic -"Improving Safety for Driverless City Vehicles: Real time communication and decision making", *IEEE June 2012.*

[6] Vicente Milanes, Enrique Onieva, Joshue Perez, and Jorge Godoy - "An Approach to Driverless Vehicles in Highways" , *IEEE 2011*

[7] Milos Mladenovic and Montasir Abbas "Self-organizing Control Framework for Driverless Vehicles", *IEEE 2013.*

[8] G.R. Dunlop, M Jufer- "Design of Magnetic Steering Sensors for Serpentine Driverless Vehicle" - *IEEE 1998.*

[9] Sebastian Thrun's "What we're driving at". The Official Google Blog,October 11, 2010.

[10] "New Law Allows Driverless Cars On Michigan Roads". CBS Detroit. 28 December 2013. Retrieved 2 November 2014.

[11] Hung-Yih Tsai "The Design of Intelligence Vehicle's Heterogeneous Interconnection Platform."

[12] Michael J. Kelly's Intelligent Vehicle-Highway Systems (IVHS),The "I" in IVHS is Still Mostly Human Intelligence-

[13] Ravi Shanker, Adam Jonas, Scott Devitt – "Autonomous Cars Self-Driving the New Auto Industry Paradigm." , IEEE Spectrum